

IN THE CLAIMS

1. (currently amended) A method at a phone-interface device, comprising:

receiving a provisional-alarm report;

determining whether a disarm command has been received subsequent to receipt of the provisional-alarm report; ~~and~~

when a disarm command has not been received before expiration of a period of time, sending a system condition to a monitoring station including seizing a telephone line; and

calling the monitoring station via the telephone line; and

determining whether the calling element is successful, and when the calling element is not successful, sending the alarm condition to the monitoring station via an alternative communications link.

2. (original) The method of claim 1, wherein the provisional-alarm report is received via a wireless signal.

3. (original) The method of claim 2, wherein the wireless signal is a radio frequency signal.

4-6. (canceled)

7. (currently amended) A phone-interface device, comprising:

a receiver to receive a wireless signal from a control panel, wherein the wireless signal encodes information regarding a system condition; and

a phone port to connect to a communications link, wherein the phone port is to dial a telephone number of a monitoring station in response to receiving the wireless signal and the communications link is at least one of an ISDN line and wireless.

8. (original) The phone-interface device of claim 7, wherein the communications link is a telephone line.

9-10 (canceled)

11. (original) A phone-interface device, comprising:

a phone port to draw electrical energy from a phone line, wherein the phone port is part of a premise phone system, and wherein the electrical energy drawn from the phone line is within a current and voltage profile of the premise phone system.

12. (original) The phone-interface device of claim 11, further comprising:

an energy storage device, wherein the electrical energy drawn from the phone line charges the energy storage device.

13. (original) The phone-interface device of claim 12, wherein the energy storage device is a battery.

14. (original) The phone-interface device of claim 12, wherein the energy storage device is a capacitor.

15. (original) The phone-interface device of claim 12, wherein the electrical energy is drawn from the phone line during a phone line state of ringing.

16. (original) The phone-interface device of claim 12, wherein the electrical energy is drawn while a premise phone is off-hook.

17. (original) The phone-interface device of claim 12, wherein the electrical energy is drawn while the phone port checks the line for proper voltages and currents.

18. (original) The phone-interface device of claim 12, wherein the electrical energy is drawn while the phone port is dialing.

19. (original) The phone-interface device of claim 12, wherein the electrical energy is drawn during a connected call.

20. (original) The phone-interface device of claim 12, wherein the electrical energy is drawn after an off-premise call has hung up.

21. (currently amended) A security system, comprising:

a control panel to receive a sensor event from a security device, to translate the sensor event into a system condition, and to transmit a wireless signal to a phone-interface device, wherein the wireless signal encodes information regarding the system condition; and

a phone-interface device to receive the wireless signal from the control panel, wherein the phone-interface device is packaged separately from the control panel,

wherein the phone-interface device receives direct electric current from an energy storage device.

clm 24

22. (original) The security system of claim 21, wherein the phone-interface further comprises a phone port to connect to a telephone line, wherein the phone port is to dial a telephone number of a monitoring station in response to receiving the wireless signal.

23. (original) The security system of claim 21, wherein the control panel receives alternating electric current.

24. (canceled)

25. (original) The security system of claim 24, wherein the energy storage device comprises a battery.

26. (original) The security system of claim 24, wherein the energy storage device comprises a capacitor.

27. (original) The security system of claim 21, wherein the phone-interface device receives electrical power from a telephone line.

28. (original) The security system of claim 21, wherein the phone-interface device is mounted in a separate enclosure from the control panel.

29. (original) The security system of 21, wherein the phone-interface device is mounted in a separate enclosure from an input device.

30. (original) The security system of 21, wherein the phone-interface device is mounted in a separate enclosure from a siren.

31. (currently amended) A program product comprising a signal-bearing media bearing instructions, which when read and executed by a processor, comprise:

receiving a provisional-alarm report;

determining whether a disarm command has been received subsequent to receipt of the provisional-alarm report; ~~and~~

when a disarm command has not been received before expiration of a period of time, sending a system condition to a monitoring station including seizing a telephone line, and calling the monitoring station via the telephone line; and 34

determining whether the calling is successful, and when the calling is not successful, sending the alarm condition to the monitoring station via an alternative communications link. 35

32. (original) The program product of claim 31, wherein the provisional-alarm report is received via a wireless signal.

33. (original) The program product of claim 32, wherein the wireless signal is a radio frequency signal.

34-35. (canceled)